

FIRESIST® FIRE SPRINKLER PIPES



Borusan Pipe is a leading steel pipe company, manufacturing over 4.000 products at 11 world-class facilities in Türkiye, Italy, Romania, and the USA, with over 65 years of expertise.

We provide the widest range of UL listed & FM approved fire protection pipes. We offer the most suitable product for your needs: bare, galvanized, primer varnished, epoxy-coated options and roll grooved, threaded & coupled, or beveled pipe ends. We have a well-established sales organization with active sales in over 35 countries.

Borusan Pipe is determined to become the supplier of choice for your increasingly vital challenges in fire protection projects through customer-centric R&D, long-term collaboration, consistent product quality, and seamless communication. Contact us at: export@borusan.com

FIRESIST EPOXY COATED SPRINKLER PIPES

Epoxy coated Firesist pipes are certified as corrosion resistance category C3-High and proven to exhibit great mechanical performance by European independent third-party testing laboratories.

Firesist pipes are in-line with global BPA regulations and suitable for use in harsh industrial conditions with low-to-moderate salt impact.

- ❑ Powder epoxy coating up to 250 microns
- ❑ Corrosivity category C3-High certified
- ❑ Available in Red (RAL 3000) and Red Brown (RAL 3009)
- ❑ Roll grooved, threaded, coupled or beveled pipe end
- ❑ Eliminates field painting
- ❑ Widest range of UL and FM approval, CE certified
- ❑ Produced according to ASTM and EN standards
- ❑ Pressure ratings exceeding 300 psi
- ❑ Size range between 1/2" – 12"
- ❑ Reliable in all sizes
- ❑ Inner weld seam removal and custom length upon request
- ❑ Tight tolerances, consistent roundness and straightness



FIRESIST PRIMER VARNISHED SPRINKLER PIPES

Primer varnished sprinkler pipes provide protection against corrosion with low overhead cost.

- ❑ Varnishing between 20 – 25 microns
- ❑ Protects from atmospheric rust
- ❑ Available in Black (RAL 9005), Gray (RAL 7012), Red (RAL 3000), Red Brown (RAL 3009), Signal Blue (Ral 5005) and Moss Green (Ral 6005)
- ❑ Roll grooved, threaded, coupled or beveled pipe end
- ❑ Saves time, labor, cost and scrap
- ❑ Inner weld seam removal and custom length upon request

*Please contact the sales team for different RAL code requests.



GALVANIZED SPRINKLER PIPES

Zinc coated sprinkler pipes provide long lasting protection against corrosion.

They are compatible for use in wet, dry, pre-action and deluge sprinkler systems.

- ❑ Superior Zinc coating between 50 – 55 microns
- ❑ Maintains corrosion resistance
- ❑ Roll grooved, threaded, coupled or beveled pipe end
- ❑ Easy to weld and install
- ❑ Compliant with European project requirements
- ❑ Inner weld seam removal and custom length upon request



ASTM & EN EASY FLOW NON THREADABLE LIGHTWALL

	OD (mm)	OD (inch)	Wall Thickness (mm)	Wall Thickness (inch)	Weight (kg/m)	Weight (lb/ft)	UL	FM
EASY FLOW LIGHTWALL	33,7	1"	2	0,079	1,56	1,05		✓
	33,7	1"	2,60	0,102	1,99	1,34		✓
	42,4	1 1/4"	2,00	0,079	1,99	1,34		✓
	42,4	1 1/4"	2,30	0,091	2,27	1,53		✓
	42,4	1 1/4"	2,60	0,102	2,55	1,71		✓
	48,3	1 1/2"	2,00	0,079	2,28	1,53		✓
	48,3	1 1/2"	2,30	0,091	2,61	1,75		✓
	48,3	1 1/2"	2,60	0,102	2,93	1,97		✓
	60,3	1 1/2"	2,00	0,079	2,88	1,93		✓
	60,3	2"	2,60	0,102	3,70	2,49		✓
	60,3	2"	2,90	0,114	4,10	2,76		✓
	76,1	2 1/2"	2,18	0,086	3,97	2,67		✓
	76,1	2 1/2"	2,60	0,102	4,71	3,17		✓
	76,1	2 1/2"	2,90	0,114	5,23	3,52		✓
	88,9	3"	2,36	0,093	5,04	3,38		✓
	88,9	3"	2,90	0,114	6,15	4,13		✓
	88,9	3"	3,20	0,126	6,76	4,54		✓
	114,3	4"	2,60	0,102	7,16	4,81		✓
114,3	4"	3,60	0,142	9,83	6,60		✓	
139,7	5"	3,40	0,134	11,43	7,68		✓	
SCH 7	33,4	1"	2,00	0,079	1,55	1,04	✓	✓
	42,2	1 1/4"	2,00	0,079	1,98	1,33	✓	✓
	48,3	1 1/2"	2,13	0,084	2,42	1,62	✓	✓
	60,3	2"	2,13	0,084	3,05	2,05	✓	✓
	73	2 1/2"	2,18	0,086	3,80	2,55	✓	✓
	88,9	3"	2,36	0,093	5,04	3,38	✓	✓
	114,3	4"	2,60	0,102	7,16	4,81	✓	✓
	141,3	5"	3,40	0,134	11,56	7,76	✓	✓
SCH 10	26,7	3/4"	2,11	0,083	1,28	0,86	✓	✓
	33,4	1"	2,77	0,109	2,09	1,41	✓	✓
	42,2	1 1/4"	2,77	0,109	2,69	1,81	✓	✓
	48,3	1 1/2"	2,77	0,109	3,11	2,09	✓	✓
	60,3	2"	2,77	0,109	3,93	2,64	✓	✓
	73	2 1/2"	3,05	0,120	5,26	3,53	✓	✓
	88,9	3"	3,05	0,120	6,46	4,34	✓	✓
	101,6	3 1/2"	3,05	0,120	7,41	4,98	✓	✓
	114,3	4"	3,05	0,120	8,37	5,62	✓	✓
	139,7	5 1/2"	3,6	0,142	12,08	8,12	✓	✓
	141,3	5"	3,4	0,134	11,58	7,78	✓	✓
	168,3	6"	3,4	0,134	13,85	9,30	✓	✓
	219,1	8"	3,76	0,148	19,97	13,4	✓	✓
	219,1	8"	4,78	0,188	25,26	16,96	✓	✓
273,1	10"	4,19	0,165	27,79	18,67	✓	✓	
273,1	10"	4,78	0,188	31,62	21,23	✓	✓	
323,8	12"	4,78	0,188	37,61	25,28	✓	✓	
SCH 30	33,4	1"	2,90	0,114	2,18	1,46		✓
	42,2	1 1/4"	2,97	0,117	2,87	1,93		✓
	48,3	1 1/2"	3,18	0,125	3,53	2,37		✓
	60,3	2"	3,18	0,125	4,48	3,00		✓
	73	2 1/2"	4,78	0,188	8,04	5,40		✓
	88,9	3"	4,78	0,188	9,92	6,65		✓
	101,6	3 1/2"	4,78	0,188	11,41	7,65		✓
	114,3	4"	4,78	0,188	12,91	8,66		✓
	141,3	5"	5,56	0,219	18,61	12,51		✓
	168,3	6"	5,56	0,219	22,31	15,00		✓
	219,1	8"	7,04	0,277	36,82	24,72		✓
273,1	10"	7,8	0,307	51,05	34,27		✓	
SCH 40	21,3	1/2"	2,77	0,109	1,27	0,85	✓	✓
	26,7	3/4"	2,87	0,113	1,69	1,13	✓	✓
	33,4	1"	3,38	0,133	2,50	1,68	✓	✓
	42,2	1 1/4"	3,56	0,140	3,39	2,27	✓	✓
	48,3	1 1/2"	3,68	0,145	4,05	2,72	✓	✓
	60,3	2"	3,91	0,154	5,45	3,66	✓	✓
	73	2 1/2"	5,16	0,203	8,64	5,80	✓	✓
	88,9	3"	5,49	0,216	11,29	7,58	✓	✓
	101,6	3 1/2"	5,74	0,226	13,58	9,12	✓	✓
	114,3	4"	6,02	0,237	16,09	10,80	✓	✓
	141,3	5"	6,55	0,258	21,79	14,63	✓	✓
	168,3	6"	7,11	0,280	28,29	18,99	✓	✓
219,1	8"	8,18	0,322	45,34	30,45	✓	✓	
273,1	10"	9,27	0,365	60,29	40,52	✓	✓	
SCH 80	21,3	1/2"	3,73	0,147	1,62	1,09		✓
	26,7	3/4"	3,91	0,154	2,20	1,48		✓
	33,4	1"	4,55	0,179	3,25	2,19		✓
	42,2	1 1/4"	4,85	0,191	4,49	3,03		✓
	48,3	1 1/2"	5,08	0,200	5,39	3,65		✓
	60,3	2"	5,54	0,218	7,55	5,08		✓
	73	2 1/2"	7,01	0,276	11,52	7,75		✓
	88,9	3"	7,62	0,300	15,39	10,35		✓
	101,6	3 1/2"	8,08	0,318	18,82	12,67		✓
	114,3	4"	8,56	0,337	22,60	15,20		✓
	141,3	5"	9,52	0,375	31,42	21,04		✓
168,3	6"	10,97	0,432	43,05	28,88		✓	
219,1	8"	12,70	0,500	65,41	44,00		✓	

EN 10255 UL & FM

	OD (mm)	OD (inch)	Wall Thickness (mm)	Wall Thickness (inch)	UL	FM
EN 10255 Medium	21,3	1/2"	2,6	0,102		
	26,9	3/4"	2,6	0,102		
	33,7	1"	3,2	0,126		✓
	42,4	1 1/4"	3,2	0,126	✓	✓
	48,3	1 1/2"	3,2	0,126	✓	✓
	60,3	2"	3,6	0,142	✓	✓
	76,1	2 1/2"	3,6	0,142	✓	✓
	88,9	3"	4	0,157	✓	✓
	114,3	4"	4,5	0,177	✓	✓
	139,7	5"	5	0,197	✓	✓
165,1	6"	5	0,197	✓	✓	

	OD (mm)	OD (inch)	Wall Thickness (mm)	Wall Thickness (inch)	FM
EN 10255 Heavy	21,3	1/2"	3,2	0,126	✓
	26,9	3/4"	3,2	0,126	✓
	33,7	1"	4	0,157	✓
	42,4	1 1/4"	4	0,157	✓
	48,3	1 1/2"	4	0,157	✓
	60,3	2"	4,5	0,177	✓
	76,1	2 1/2"	4,5	0,177	✓
	88,9	3"	5	0,197	✓
	114,3	4"	5,4	0,213	✓
	139,7	5"	5,4	0,213	✓
165,1	6"	5,4	0,213	✓	



pipe@borusan.com
www.borusanpipe.com
+90 (549) 393 58 00

Facebook: /Borusanpipe
Instagram: /Borusanpipe
LinkedIn: /Borusanpipe
YouTube: /Borusanpipe
Twitter: /Borusanpipe